

PRODUCT DATA SHEET

For further information or assistance, contact: NCP Chlorchem Specialities Division
PO Box 150 Kempton Park 1620 • Tel: 011 921 3334 Fax: 011 976 4736



LIQUID CHLORINE (Cl₂)

TDS 002/R0
2024-04-02

LIQUID CHLORINE is a heavy, toxic, greenish yellow liquid under pressure having pungent and suffocating odour: Minimum 99.5% pure.

APPLICATION

- Water and disinfecting agent
- PVC manufacture
- Manufacture of synthetic rubber
- Chlorinated hydrocarbons
- Chlorinated paraffins
- Bleaching agent
- Waste and sewerage treatment
- Sanitizing agent

LIQUID CHLORINE, although packed in cylinders and drum under pressure, is usually used as a gas obtained by evaporation of liquid from the cylinder. It is a stable compound under atmospheric temperature and pressure. This product is approved by NSF/ANSI Standard 60 for the treatment of potable water supplies at dosages up to 30 mg/l. N.B. Always store chlorine cylinders (70 kg) in an upright position and drums (900, 925, 940, 990kg) on their sides. Keep full and empty containers separated.

TYPICAL PROPERTIES

Appearance : Greenish-yellow gas (liquid)

Chlorine concentration (%v/v): 99.5% min

Complies with SABS CKS 6.

CP Chlorine is free of toxic materials such as CYANIDE, LEAD, & MERCURY, etc.

TECHNICAL SERVICE

The Specialities division has a team of technical experts who will undertake all the necessary investigations and trials to ensure that you obtain the most effective treatment solutions. To ensure the best results are achieved optimum product dosage and ideal plant conditions are required.

OTHER PRODUCTS

NCP Chlorchem specialises in a wide range of products. The range includes:

POLYAMINES

POLYDADMACS

ALUMINIUM CHLOROHYDRATE

ALUMINIUM CHLOROHYDRATE/POLYAMINE BLENDS

ALUMINIUM CHLOROHYDRATE/POLYDADMAC BLENDS

FERRIC CHLORIDE

FERROUS CHLORIDE

CAUSTIC SODA LYE (NaOH)

HYDROCHLORIC ACID

SODIUM HYPOCHLORITE